

#	RO40401	RO40402	RO40403	RO40404	RO40405	RO40406	RO40407	RO40408
Abmessungen Rahmen in mm	400x400x1355	400x650x1355	400x650x1355	400x730x1355	400x1000x1355	400x1200x1355	800x800x1355	800x800x1355
Elektroanschluss	230V AC 50Hz 700 Watt	400VAC 50Hz 2,2 Kw	400VAC 50Hz 2,2 Kw	400VAC 50Hz 2,2 Kw	400VAC 50Hz 2,2 Kw	400VAC 50Hz 2,2 Kw	400VAC 50Hz 2,2 Kw	400VAC 50Hz 2,2 Kw
Ausbeute bei 0° dH	80%	80%	80%	80%	80%	80%	80%	80%
Ausbeute bei 12° dH	50%	50%	50%	50%	50%	50%	50%	50%
Druck Min.	1 bar (0,5 bar)	1 bar (0,5 bar)	1 bar (0,5 bar)	1 bar (0,5 bar)	1 bar (0,5 bar)	1 bar (0,5 bar)	1 bar (0,5 bar)	1 bar (0,5 bar)
Gewicht	ca. 40 Kg	ca. 55 Kg	ca. 70 Kg	ca. 85 Kg	ca. 100 Kg	ca. 115 Kg	ca. 128 Kg	ca. 145 Kg
#	RO40211	RO40212	RO40213					
Abmessungen	400x400x850	400x650x850	400x650x850					
Elektroanschluss	230V AC 50Hz 700 Watt	230V AC 50Hz 700 Watt	230V AC 50Hz 700 Watt					
Ausbeute bei 0° dH	80%	80%	80%					
Ausbeute bei 12° dH	50%	50%	50%					
Druck Min.	1 bar (0,5 bar)	1 bar (0,5 bar)	1 bar (0,5 bar)					
Gewicht	ca. 30 Kg	ca. 42 Kg	ca. 55 Kg					

